# Lined Instrument Tee

# ANSI B16.5 - Class 150#

January, 2022

### **MATERIAL**

- Lining PE-X ASTM D1998-04
- Body St 37.0-DIN 1629

# Available on request:

- Teflon lining.
- · One or two loose flanges.
- ANSI B16.5 Class 300 flanges.
- Stainless steel body and flanges 304/316.
- Different lengths (L).


### **SPECIFICATIONS**


## **Temperature limits:**

- PE-X: -30° to +90°C
- Teflon: Up to 110°C

#### **NOTES**

- Lined pipes and fittings made with PE-X inner coating can be manufactured in diameters from 2" and up to 24".
- Lined pipes and fittings made with Teflon inner coating can be manufactured in diameters from 1" and up to 24".
- For lined pipes or fittings in lower/higher diameters please consult with Golan.







Cat No.	DN 1 Inch	DN 2 Inch	L mm	Pex Lining Thickness	Weight
Pex-LIT-15025-25	1"	1"	50	4.0	2.2
Pex-LIT-15032-25	1 1/4"	1"	50	4.0	2.5
Pex-LIT-15038-12	1 ½"	1/2"		4.0	2.4
Pex-LIT-15038-19		3/4"	50		2.6
Pex-LIT-15038-25		1"			2.8
Pex-LIT-15038-38		1 1/2"	75		4.4
Pex-LIT-15050-25	2"	1"	50	4.0	3.6
Pex-LIT-15050-38		1 1/2"	75		6.2
Pex-LIT-15050-50		2"	90		8.1
Pex-LIT-15062-25	2 ½"	1"	50		3.9
Pex-LIT-15062-38		1 1/2"	75	4.0	7.2
Pex-LIT-15062-50		2"	90		9.8
Pex-LIT-15080-25	3"	1"	50	4.0	4.7
Pex-LIT-15080-38		1 1/2"	75		8.3
Pex-LIT-15080-50		2"	90		12.6
Pex-LIT-150100-25	4"	1"	50	4.0	5.9
Pex-LIT-150100-38		1 1/2"	75		8.9
Pex-LIT-150100-50		2"	90		16.0
Pex-LIT-150100-80		3"	130		24.5
Pex-LIT-150150-25	6"	1"	50	4.0	8.2
Pex-LIT-150150-38		1 1/2"	75		14.7
Pex-LIT-150150-50		2"	90		21.8
Pex-LIT-150150-80		3"	130		30.1
Pex-LIT-150200-25		1"	50	4.0	10.5
Pex-LIT-150200-38	8"	1 1/2"	75		17.8
Pex-LIT-150200-50		2"	90		23.3
Pex-LIT-150200-80		3"	130		33.3



Cat No.	DN 1 Inch	DN 2 Inch	L mm	Pex Lining Thickness	Weight
Pex-LIT-150100-25	10"	1"	50	4.0	13.7
Pex-LIT-150100-38		1 1/2"	75		23.3
Pex-LIT-150100-50		2"	90		26.0
Pex-LIT-150100-80		3"	160		36.7
Pex-LIT-150100-25	12"	1"	50	4.0	43.0
Pex-LIT-150100-38		1 1/2"	75		55.5
Pex-LIT-150100-50		2"	90		62.0
Pex-LIT-150100-80		3"	160		69.0
Pex-LIT-150100-25	14"	1"	50	4.0	53.1
Pex-LIT-150100-38		1 1/2"	75		66.5
Pex-LIT-150100-50		2"	90		73.7
Pex-LIT-150100-80		3"	160		103.0
Pex-LIT-150100-25	16"	1"	90	4.0	59.0
Pex-LIT-150100-38		1 1/2"	110		74.0
Pex-LIT-150100-50		2"	120		83.0
Pex-LIT-150100-80		3"	160		116.7
Pex-LIT-150100-25	18"	1"	90	4.0	68.5
Pex-LIT-150100-38		1 1/2"	110		90.5
Pex-LIT-150100-50		2"	120		93.7
Pex-LIT-150100-80		3"	160		129.7
Pex-LIT-150100-19	20"		0.0	4.0	Χ
Pex-LIT-150100-25		1"	90		72.0
Pex-LIT-150100-38		1 1/2"	110		89.7
Pex-LIT-150100-50		2"	120		100.0
Pex-LIT-150100-80		3"	160		137.0
Pex-LIT-150100-25	24"	1"	90	4.0	79.1
Pex-LIT-150100-38		1 1/2"	110		94.5
Pex-LIT-150100-50		2"	120		107.5
Pex-LIT-150100-80		3"	160		150.0

